









Specifications		Connector	Dimensions																																																																																										
Sensor	ICX 285	<p>DC-In / Trigger</p>  <p>Hirose HR10A-10P-12S</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Signal</th> <th>Function</th> </tr> </thead> <tbody> <tr><td>1</td><td>GND</td><td>GROUND</td></tr> <tr><td>2</td><td>Vin</td><td>+15-24V</td></tr> <tr><td>3</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>4</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>5</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>6</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>7</td><td>Trigger in</td><td>Input trigger</td></tr> <tr><td>8</td><td>Trigger out</td><td>Output trigger</td></tr> <tr><td>9</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>10</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>11</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>12</td><td>DNC</td><td>Do not connect</td></tr> </tbody> </table> <p>Camera Link Interface 26 pin MDR connector 3M 10226-1A10JL</p>  <table border="1"> <thead> <tr> <th>Pin</th> <th>Signal</th> <th>Function</th> </tr> </thead> <tbody> <tr><td>1</td><td>14</td><td>GND</td></tr> <tr><td>2</td><td>15</td><td>X0-/X0+</td><td>CL Data</td></tr> <tr><td>3</td><td>16</td><td>X1-/X1+</td><td>CL Data</td></tr> <tr><td>4</td><td>17</td><td>X2-/X2+</td><td>CL Data</td></tr> <tr><td>5</td><td>18</td><td>Xclk-/Xclk+</td><td>CL Clk</td></tr> <tr><td>6</td><td>19</td><td>X3-/X3+</td><td>CL Data</td></tr> <tr><td>7</td><td>20</td><td>Ser TC+/Ser TC-</td><td>Serial in</td></tr> <tr><td>8</td><td>21</td><td>Ser TFG+/Ser TFG-</td><td>Serial out</td></tr> <tr><td>9</td><td>22</td><td>CC1-/CC1+</td><td rowspan="3">Not Used</td></tr> <tr><td>10</td><td>23</td><td>CC2-/CC2+</td></tr> <tr><td>11</td><td>24</td><td>CC3-/CC3+</td></tr> <tr><td>12</td><td>25</td><td>CC4-/CC4+</td><td rowspan="2">Not Used</td></tr> <tr><td>13</td><td>26</td><td>GND</td></tr> </tbody> </table>	Pin	Signal	Function	1	GND	GROUND	2	Vin	+15-24V	3	DNC	Do not connect	4	DNC	Do not connect	5	DNC	Do not connect	6	DNC	Do not connect	7	Trigger in	Input trigger	8	Trigger out	Output trigger	9	DNC	Do not connect	10	DNC	Do not connect	11	DNC	Do not connect	12	DNC	Do not connect	Pin	Signal	Function	1	14	GND	2	15	X0-/X0+	CL Data	3	16	X1-/X1+	CL Data	4	17	X2-/X2+	CL Data	5	18	Xclk-/Xclk+	CL Clk	6	19	X3-/X3+	CL Data	7	20	Ser TC+/Ser TC-	Serial in	8	21	Ser TFG+/Ser TFG-	Serial out	9	22	CC1-/CC1+	Not Used	10	23	CC2-/CC2+	11	24	CC3-/CC3+	12	25	CC4-/CC4+	Not Used	13	26	GND	  
Pin	Signal		Function																																																																																										
1	GND		GROUND																																																																																										
2	Vin		+15-24V																																																																																										
3	DNC		Do not connect																																																																																										
4	DNC		Do not connect																																																																																										
5	DNC		Do not connect																																																																																										
6	DNC		Do not connect																																																																																										
7	Trigger in		Input trigger																																																																																										
8	Trigger out		Output trigger																																																																																										
9	DNC		Do not connect																																																																																										
10	DNC		Do not connect																																																																																										
11	DNC	Do not connect																																																																																											
12	DNC	Do not connect																																																																																											
Pin	Signal	Function																																																																																											
1	14	GND																																																																																											
2	15	X0-/X0+	CL Data																																																																																										
3	16	X1-/X1+	CL Data																																																																																										
4	17	X2-/X2+	CL Data																																																																																										
5	18	Xclk-/Xclk+	CL Clk																																																																																										
6	19	X3-/X3+	CL Data																																																																																										
7	20	Ser TC+/Ser TC-	Serial in																																																																																										
8	21	Ser TFG+/Ser TFG-	Serial out																																																																																										
9	22	CC1-/CC1+	Not Used																																																																																										
10	23	CC2-/CC2+																																																																																											
11	24	CC3-/CC3+																																																																																											
12	25	CC4-/CC4+	Not Used																																																																																										
13	26	GND																																																																																											
Active area	2/3" sensor 10.2 mm(H) x8.3 mm (V)																																																																																												
Pixel size	6.45µm																																																																																												
Pixel clock	20 MHz																																																																																												
Active pixels	1360 x 1024																																																																																												
Frame rate	15 Fps full resolution																																																																																												
Channels	Channel 1: 400 – 670 nm Channel 2: 670 – 850 nm Channel 3: 850 – 1000 nm																																																																																												
Alignment accuracy	Mechanically better than 1/4 th of a pixel																																																																																												
Dynamic range	>56 dB																																																																																												
Bit depths	8 bit 3 channel, 12 bit 3 channel																																																																																												
Gain	0 to 36 dB analog gain																																																																																												
Video output	Camera Link Base / GigE Vision																																																																																												
Trigger modes	Internal and external source (on CameraLink and Hirose connectors)																																																																																												
Synchronization	All sensor clocks synchronized. Smart trigger unit for advanced trigger schemes																																																																																												
Electronic shutter	Synchronized exposure with channel independent duration. (1 µs to 1s)																																																																																												
Control interface	All commands through Camera Link serial interface																																																																																												
Lookup tables	Lookup tables available in 8bit mode, full access to table entries. Table data programmed in flash memory (on request)																																																																																												
External control capability *)Selectable per channel	Gain*, exposure*, lookup tables*, region of interest, image bit depth, trigger source																																																																																												
Weight	785 grams excluding lens																																																																																												
Dimensions	100x78X124 mm																																																																																												
Lens mount options	F-Mount or M42 custom lens																																																																																												
Operating temperature	-20 - +50 °C																																																																																												
Regulations	CE (EN 61000-6-2 EN 61000-6-3), FCC Part 15 class B, RoHS/WEE																																																																																												
Back focal length	≥ 46.50 mm in air																																																																																												
Power	18-24V DC +/-10%, 9W																																																																																												
Humidity	20-90% Non condensing																																																																																												



Examples

1. Original prism dichroic coating
2. Optional narrow band filter in channel 3
3. Optional narrow band filter in channel 2
4. Optional narrow band filter in channel 2 and 3

Filters can be customized on user requirements