

Still Using Frame Grabbers?

30FPS 0.33M pixels CCD progressive USB2.0 COLOR (mono) CCD CAMERA

Connect USB2.0 camera to your PC via USB2.0 interface.

Image capture board NOT required.

Save image directly to your PC with high speed transfer.

Features

- *0.33M pixels Inter-line CCD sensor
- *Gain control & Shutter control
- *High speed bayer conversion allowed by SSE2
- *SDK (Software Development Kit) available
- *Capture image at 10 bits (SDK)
- *Frame rate VGA : 30FPS
- *Low price
- *Monochrome available ARTCAM-098-BW

Specifications

- *Maximum resolution : 640 x 480
- *Pixel size : 5.6 x 5.6 μ m
- *Type of CCD : Inter-line model
- *Sensitivity : 2.7V/Lux-sec(@550nm)
- *S/N : 48dB or higher
- *Lens mount : C mount (lens is not included)
- *Optical size : 1/4"
- *Image area size : 4.6 x 3.97mm
- *Dimension : 50(W)x56(H) x59.3(D)mm
- *Power : Supplied from USB port

Board Cameras Available



ARTCAM-098-OP-CM

ARTCAM-098-OP

Minimum System Requirements :

Windows 2000/XP, CPU 1.7GHz, Memory 512MB

ARTRAY

ARTCAM-098



ARTRAY INC. U.S.A. OFFICE
646 NE Josephine Ct., Hillsboro, OR 97124, U.S.A.
TEL: 503-380-7809 FAX: 503-648-4233
URL: <http://www.artray.us> E-mail: sales@artray.us

ARTRAY CO., LTD TOKYO HEAD OFFICE
Ueno bldg, 1-17-5 koudenjikota Suginami-ku Tokyo 166-0002, Japan
TEL: +81-3-3389-5488 FAX: +81-3-3389-5486
URL: <http://www.artray.co.jp> E-mail: artray@artray.co.jp