



| | | | | | | | | | | | | |
|--------|----------------|----------|-------|----------|---------|---|-----------|-----------------|-----------|-----------------------------------|----------|---------------|
| △× | | | | APPROVED | CHECKED | MATERIAL 材料 | - | CHAMFER 一般面取 | - | QUANTITY 個数 | | |
| △× | | | | T. A. | T. A. | TREATMENT 処理 | - | FINISHING 仕上 | - | - | | |
| △× | | | | | | TREATMENT CONTACT 処理接点 | - | DECENTRATION 偏芯 | - | - | | |
| △× 3 | ホルト 範囲・外径寸法追加 | 20.10.08 | R. H. | DESIGNED | DRAWN | OVER 250 UP TO 1000 ±0.3 ±0.5 ±1.0 ±0.2 | UNIT (mm) | ANGLE 角度 | | REMARK 適用 (機種名) VS-TCM01-180/S | | |
| △× 1 | Iris ring 表記追加 | 19.03.03 | T. F. | T. A. | T. T. | OVER 63 UP TO 250 ±0.2 ±0.3 ±0.6 ±0.15 | | - | METHOD 図法 | | | |
| | | | | | | OVER 16 UP TO 63 ±0.1 ±0.2 ±0.4 ±0.1 | | SCALE | 1 / 1 | | NAME | DRAWING / 外觀図 |
| | | | | | | OVER 0 UP TO 16 ±0.05 ±0.1 ±0.2 ±0.1 | | DATE | '11.11.04 | | DRAW NO. | ODTC0482A3 |
| NO.×箇所 | REVISION 訂正事項 | DATE | NAME | | | TOLERANCES A B C S | | | | | | |