Metaphase Technologies, Inc.

MetalightTM Linear Front Light Model#: LFL2X8



- Shock and Vibration proof up to 10 G's per MIL-STD-910F the highest industry standards
- · Solid one-piece machined aluminum housings and thermal potting
- · Performance extends to rugged environments
- · Can be configured for wavelength and other specifications
- · Equipt with pairing and axial rotation capabilities

Part #	Color	Power Supply
LFL2X8-W-24	White 5500K	
LFL2X8-R-24	Red 630nm	
LFL2X8-B-24	Blue 455nm	
LFL2X8-G-24	Green 530nm	24 volt power supply available
LFL2X8-IRN-24	Infrared 850nm	upon request.
LFL2X8-IRL-24	Infrared 880nm	
LFL2X8-UVL-24	UV 395nm	
LFL2X8-UVS-24	UV 365nm	

10 ft. flying leads come standard on all products. Light features built-in constant current driver. No expensive controller required.

Specifications:	
Current Consumption	0.9A @ 24VDC
Housing	Aluminum
Finish	Anodized
Intensity Uniformity	+/-5%
Operating Temperature	120° F Max
Illuminance	75,000 Lux
Compliance	CE/RoHS
Lifetime Hours	75,000 Hours

Active Area	Dimensions
1 in x 65 in	66.81in x 1.13in x 1.25in
25.4mm x 1651mm	1696mm x 28.58mm x 31.75mm





MetaLight™ Linear Front Light Model#: LFL2X8

M′	12 Connector
PIN#	Function
1	+24VDC
2	0-10VDC Intensity Control
3	Ground
4	Signal Ground

Wiring Diagram		
Flying Leads	Function	
RED	+24VDC	
BLACK	Ground	
WHITE	+24VDC	
GREEN	Ground	
24 AVAC 4 VALIDEC CARLE V 1		

24 AWG 4 WIRES CABLE X 1

When not using intensity control, connect 0-10V control line to +24 (Max Intensity Control = 25V) and intensity control ground to ground

