MetaBright™ Area Backlight Model#: MB-BL12X12





- Up to 50 SMD LED's per inch array makes our backlights the brightest most stable backlights in the industry
- Exclusive optical lens producing even (+/- 5%), shadow-free illumination
- · High Density Precision Chip technology
- · Patent-pending thermal management design draws heat directly from the die ensuring long life
- · Stable, flicker-free illumination with instant-start operation

V	Viring Diagram	M1	2 Connector	Specifications:	Specifications:	
Flying Leads	Function	PIN #	Function	Current Consumption	• -	
RED	+24VDC	1	+24VDC	Finish	Aluminum Powder Coated Black	
BLACK	Ground	3	Ground	Intensity Uniformity	+/-5%	
WHITE	NHITE 0~10V		6 6 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	Illuminance	38,000 Lux	
GREEN	Signal Ground			Operating Temperatu Compliance	re 120° F Max CE/RoHS	
		2		Lifetime Hours	75,000 Hours	
		((0 5			
		Vo	● NC	Active Area	Dimensions	
		3	4	12in x 12in 304.8mm x 304.8mm	15in x 14.25in x 0.87in 381mm x 361.95mm x 22mm	

ORDERING INFORMATION:									
• M B - B L 1 2 X 1 2	- W R G B IR UVL UVS	- 2 4 - White 6000k Red 630nm Green 530nm Blue 455 nm Infrared 880nm (long) 395nm (short) 365nm	 *BLANK T ILD ILS	10 ft. Flying Leads M12 Quick Disconnect In Line Dimmer In Line Strobe (customer provide trigger info)					

metaphase-tech.com

MetaBright™ Area Backlight Model#: MB-BL12X12



Contact us:

Contact your Metaphase Technologies Representative for options including: Diffuser Choice, Polarizer & Light Control Film, Specific Intensity & Uniformity, & Wavelength.

