

MetaBright™ Diffuse Axial Light

Model#: DAL205



- Size: 2 x 2 in active area
- Over thirty five SMD per inch array makes our diffuse axial lights the brightest most stable coaxial lighting in the industry
- 6 different sizes of diffuse axis light models to fit different application needs
- Exclusive optical beam splitter and diffuser stack
- Machined aluminum housing with optional dust covers

Specifications:

Current Consumption	R: 0.2A W/G/B: 0.21A
Housing	Alluminum
Finish	Powder Coated Black
Intensity Uniformity	+/-5%
Weight	2lbs / 0.9kg
Operating Temperature	120° F Max
Illuminance	36,000 Lux
Compliance	CE/RoHS
Lifetime Hours	75,000 Hours

Wiring Diagram

Flying Leads	Function
RED	+24VDC
BLACK	Ground

24 AWG 4 WIRES CABLE X 1
When not using intensity control, connect 0-10V control line to +24 (Max Intensity Control = 25V) and intensity control ground to ground


Active Area

Dimensions

2 x 2in	2.32in x 4.30in x 2.28in
50.8mm x 50.8mm	58.9mm x 109.2mm x 57.9mm

M12 Connector

PIN #	Function
1	+24VDC
3	Ground



ORDERING INFORMATION:

• D A L 2 0 5 - - 2 4 -

W	White 6000k	*BLANK	10 ft. Flying Leads
R	Red 630nm	T	M12 Quick Disconnect
G	Green 530nm	ILD	In Line Dimmer
B	Blue 455 nm	ILS	In Line Strobe (customer provide trigger info)
IRN	Infrared 850nm		
RGB	625/530/70nm		

MetaBright™ Diffuse Axial Light Model#: DAL205

Contact us:

Contact your Metaphase Technologies Representative for options including: Diffuser Choice, Polarizer & Light Control Film, Specific Intensity & Uniformity, & Wavelength.

Drawing/Diagram

