MetaBright™ High Power Diffuse Dome Light



Model#: MB-DL406



- Size: 7" I.D./10" O.D.
- Patent-pending LED heat management for consistent performance
- · High intensity and uniform, non-directional illumination across entire lighting hemisphere for area scan
- Ideal for highly reflective surfaces and textured or topographic objects
- Provides cloudy day illumination, minimizing shadows and glare
- Enclosed workspace blocks interference of ambient light
- Optical grade reflector coating reflects 99.9% of light for optimum diffused output
- · Strobe & dimming options
- Mounting: Comes with mounting studs


Specifications:	
Current Consumption	1.59A
Housing	Aluminium
Finish	Powder Coated Black
Intensity Uniformity	+/-5%
Operating Temperature	120° F Max
Illuminance	68,000 Lux
Compliance	CE/RoHS
Lifetime Hours	75,000 Hours

Wiring Diagram		
Flying Leads	Function	
RED	+24VDC	
WHITE	0~10V	
BLACK	Ground	
GREEN	Signal Ground	
	24 AWG 4 WIRES CARLE X 1	

24 AWG 4 WIRES CABLE X 1	
When not using intensity control, connect 0-10V	
control line to +24 (Max Intensity Control = 25V)	
and intensity control ground to ground	

M12 Connector		
PIN#	Function	
1	+24VDC	
2	0-10VDC Intensity Control	
3	Ground	
4	Signal Ground	





ORDERING INFORMATION: • MB - DL 406 - 24 -10 ft. Flying Leads *BLANK W White 6000k T M12 Quick Disconnect R Red 630nm G **ILD** Green 530nm ILS In Line Strobe (customer provide trigger info) В Blue 455 nm IRN Infrared 850nm LL Long Focal Lens

MetaBright™ High Power Diffuse Dome Light

Metaphase Technologies, Inc.

Model#: MB-DL406

