

MetaBright™ Linear Backlight

Model#: MB-LBL202



- Configurable for various wavelengths
- Stable, flicker-free illumination with instant-start operation
- 35 SMT array LED providing maximum intensity area with +/- 0.5% uniformity
- High Density Precision Chips Tehcnology (HDPCT)
- Patent-pending thermal management design draws heat directly from the die ensuring long life

Active Area Dimensions

1.2 in x 6 in 2.5 x 8.22 x 0.71 in
30.48mm x 152.4mm 63.5mm x 208.7mm x 18mm

Part # Color

MB-LBL202-W-24	White 6000 K
MB-LBL202-R-24	Red 630nm
MB-LBL202-B-24	Blue 455nm
MB-LBL202-G-24	Green 530nm
MB-LBL202-IRN-24	Infrared 850nm
MB-LBL202-IRL-24	Infrared 880nm
MB-LBL202-UVL-24	UV 395nm
MB-LBL202-UVS-24	UV 365nm

Specifications:


Current Consumption	RED: 0.4A W/B/G: 0.6A
Housing	Aluminum
Casing	Stainless Steel
Finish	Powder Coated Black
Intensity Uniformity	+/-5%
Operating Temperature	120° F Max
Illuminance	36,000 Lux
Compliance	CE/RoHS
Lifetime Hours	75,000 Hours

Wiring Diagram

Flying Leads	Function
RED	+24VDC
BLACK	Ground

M12 Connector

PIN #	Function
1	+24VDC
3	Ground



ORDERING INFORMATION:

• M B - L B L 2 0 2 - □ - 2 4 - □

W	White 5500k	*BLANK	10 ft. Flying Leads
R	Red 630nm	T	M12 Quick Disconnect
G	Green 530nm	ILD	In Line Dimmer
B	Blue 455 nm	ILS	In Line Strobe (customer provide trigger info)
IRL	Infrared 880nm		
UVL	(long) 395nm		
UVS	(short) 365nm		

MetaBright™ Linear Backlight Model#: MB-LBL202

Drawing/Diagram

