

MetaBright™ Long Range Strobe

Model#: MB-WLRS605 - Wide Beam



- NOISE FREE STROBING (SILENT OPERATION)
- POWERFUL LED TECHNOLOGY
- LONG RANGE BEAM
- LOW MAINTENANCE
- WEATHERPROOF ENCLOSURE
- NO BALLAST OR STARTER NEEDED
- NO EMI/RFI
- NO UV EMISSIONS LENS OR DIFFUSER AGING
- ULTRA-LONG-LIFE (100,000 HOURS)

Part #	Color
--------	-------

MB-WLRS605-W-24	White 6000 K
MB-WLRS605-R-24	Red 630nm
MB-WLRS605-B-24	Blue 455nm
MB-WLRS605-G-24	Green 530nm
MB-WLRS605-IRN-24	Infrared 850nm

10 ft. flying leads come standard on all products.
Light features built-in constant current driver.
No expensive controller required.

Specifications:

Current Consumption	2A
Input Voltage	24VDC
Trigger Input	5-24VDC
Trigger Type	TTL
Finish	Appliance White Powder Coating
Shock & Vibration	20,000 G's
Operating Temperature	-30° to 120°F (-34 to 48.8°C)
Flash Rate	Up to 60Hz

Contact Us:

Contact your Metaphase Technologies Representative for options including: Diffuser Choice, Polarizer & Light Control Film, Specific Intensity & Uniformity, & Wavelength.

ORDERING INFORMATION:

• M B - W L R S 6 0 5 - - 2 4 -

W White 5500k
R Red 630nm
G Green 530nm
B Blue 455 nm
IRL Infrared 880nm
UVL (long) 395nm
UVS (short) 365nm

***BLANK**
T 10 ft. Flying Leads
ILD M12 Quick Disconnect
ILS In Line Dimmer
 In Line Strobe (customer provide trigger info)

MetaBright™ Long Range Strobe Model#: MB-WLRS605 - Wide Beam

Wiring Diagram

Flying Leads	Function
Blue	Trigger Input
GREEN	Trigger Ground

Wiring Diagram

In-Line DC Jack	Function
Middle Lead	+ Positive
Side Wall	- Negative

Female RS-232 (#2 TX / #3 RX / #5 G)
For controller configuration via PC software
(Included)

Drawing/Diagram

