MetalightTM Round Area Front Light Model#: RAL105





- THE LOWEST COST SIMPLEST LED LIGHTING AVAILABLE FOR STANDARD INTENSITY FRONT LIGHTING
- AVAILABLE IN 3 DIFFERENT DIAMETERS TO SERVE VIRTUALLY ANY WORK SPACE PROVEN DESIGN WITH THOUSANDS OF INSTALLATIONS AROUND THE WORLD
- SOLID ONE-PIECE MACHINED ALUMINUM HOUSINGS AND THERMAL POTTING ASSURES LONG LIFE PERFORMANCE EVEN IN RUGGED ENVIRONMENTS
- SHOCK AND VIBRATION RESISTANT
- SOLUTION FOR ON AND OFF-AXIS VISION

Part #	Color	Power Supply
RAL105-W-24	White 6000 K	
RAL105-R-24	Red 630nm	
RAL105-B-24	Blue 455nm	
RAL105-G-24	Green 530nm	24 volt power supply available
RAL105-IRN-24	Infrared 850nm	upon request.
RAL105-IRL-24	Infrared 880nm	
RAL105-UVL-24	UV 395nm	
RAL105-UVS-24	UV 365nm	

Specifications:	
Current Consumption	0.05A
Finish	Anodized
Intensity Uniformity	+/-5%
Operating Temperature	120° F Max
Illuminance	118,000 Lux
Compliance	CE/RoHS
Lifetime Hours	75,000 Hours

10 ft. flying leads come standard on all products.
Light features built-in constant current driver.
No expensive controller required.

Active Area	Dimensions
31.75mm I.D	61.96mm x 38.10mm
1.25in I.D.	2.44in x 1.50in

ORDERING INFORMATION: • RAL105 - 24 -White 5500k *BLANK 10 ft. Flying Leads Red 630nm T. M12 Quick Disconnect Green 530nm ILD In Line Dimmer In Line Strobe (customer provide trigger info) Blue 455 nm ILS IRL Infrared 880nm **UVL** (long) 395nm UVS (short) 365nm

MetalightTM Area Front Light Model#: RAL105



	M12 Connector	
PIN	# Function	
1	+24VDC	
2	0-10VDC Intensity Control	
3	Ground	
4	Signal Ground	

Wiring Diagram				
Flying Leads	Function			
RED	+24VDC			
BLACK	Ground			
WHITE	0~10V or +24VDC			
GREEN	Ground			
24 AWG 4 WIRES CABLE X 1				

When not using intensity control, connect 0-10V control line to +24 (Max Intensity Control = 25V) and intensity control ground to ground

