



| | | | | | | | | | | | |
|---|------|----------|---------------|----------|---------|------------------------|----------------------|-----------------|-----------|-----------------|----------------|
| △ | | | | APPROVED | CHECKED | MATERIAL 材料 | - | CHAMFER 一般面取 | - | QUANTITY 个数 | |
| △ | | | | T. A. | T. A. | TREATMENT 処理 | - | FINISHING 仕上 | - | - | |
| △ | | | | | | TREATMENT CONTACT 処理接点 | - | DECENTRATION 偏芯 | - | | |
| △ | | | | DESIGNED | DRAWN | OVER 250 UP TO 1000 | ±0.3 ±0.5 ±1.0 ±0.2 | ANGLE 角度 | METHOD 図法 | REMARK 適用 (機種名) | |
| △ | | | | T. A. | T. T. | OVER 63 UP TO 250 | ±0.2 ±0.3 ±0.6 ±0.15 | - | | VS-0814H1 | |
| △ | | | | | | OVER 16 UP TO 63 | ±0.1 ±0.2 ±0.4 ±0.1 | | | | SCALE |
| △ | | | | | | OVER 0 UP TO 16 | ±0.05 ±0.1 ±0.2 ±0.1 | DATE | 13.03.18 | DRAW NO. | 01D S V 0135A1 |
| | DATE | EXCH NO. | REVISION 変更記事 | | | TOLERANCES | A B C S | | | | |