



| | | | | | | | | | | |
|---|------|----------|---------------|----------|---------|---|-----------|-----------------|-----------|-----------------|
| △ | | | | APPROVED | CHECKED | MATERIAL 材料 | | CHAMFER 一般面取 | | QUANTITY 個數 |
| △ | | | | T. A. | T. M. | TREATMENT 処理 | | FINISHING 仕上 | | |
| △ | | | | DESIGNED | DRAWN | TREATMENT CONTACT 処理接点 | | DECENTRATION 偏芯 | | |
| △ | | | | T. A. | S. K. | OVER 250 UP TO 1000 ±0.3 ±0.5 ±1.0 ±0.2 | UNIT (mm) | ANGLE 角度 | METHOD 図法 | REMARK 適用 (機種名) |
| △ | | | | | | OVER 63 UP TO 250 ±0.2 ±0.3 ±0.6 ±0.15 | | | | VSZ-M0108S |
| △ | | | | | | OVER 16 UP TO 63 ±0.1 ±0.2 ±0.4 ±0.1 | SCALE | 1 / 1 | NAME | 外觀圖 |
| △ | | | | | | OVER 0 UP TO 16 ±0.05 ±0.1 ±0.2 ±0.1 | DATE | '09.02.20 | DRAW NO. | ODMZ0060A1 |
| | DATE | EXCH NO. | REVISION 変更記事 | | | TOLERANCES | A | B | C | S |