## **Zoom Lens** ズームレンズ

## Y20Z10 (10 - 200mm) Series













| Туре                                      |                        | NEW AUTO FOCUS MODEL  |                      | REMOTE CONTROL FOCUS MODEL |                                |                      |
|---|------------------------|---|----------------------|----------------------------|--------------------------------|----------------------|
| Model No.                                 |                        | Y20Z10AFP5E   | Y20Z10AFDP5E         | Y20Z10MP5E                 | Y20Z10AP5E                     | Y20Z10ADP5E          |
| Format Size                               |                        |   | 1/                   | /2"                        |                                |                      |
| Mount                                     |                        |   | C / CS (with         | CS adapter)                |                                |                      |
| Zoom Ratio                                |                        | x20   |                      |                            |                                |                      |
| Focal Length                              |                        | 10.0-200mm  |                      |                            |                                |                      |
| Max. Aperture Ratio                       |                        | 1:2.4   |                      |                            |                                |                      |
| Iris Range                                |                        | F2.4-F78  | F2.4-F10             |                            | 4-F78                          | F2.4-F10             |
| Applicable Wavelength                     |                        |   |                      | -950nm                     |                                |                      |
| Min. Object Distance                      |                        | 1.8m  |                      |                            |                                |                      |
| ,   |                        | Diagonal / Horizontal / Vertical (4:3)                      |                      |                            |                                |                      |
| Angle of View                             | Wide                   | 42.4° / 34.8° / 26.4°                                       |                      |                            |                                |                      |
|   | Tele                   | 2.2° / 1.8° / 1.4°  |                      |                            |                                |                      |
|   | Iris                   | Auto Iris(Video) (& Remote*)                                | Auto Iris(DC)        | Remote Control             | Auto Iris(Video) (& Remote*)   | Auto Iris(DC)        |
| Operation                                 | Zoom                   | Auto ins(video) (& Hemote )                                 |                      |                            | riato instituco) (a ricinote ) | Adio Ilia(DO)        |
|   | Focus                  | Remote Control  Auto Focus & Remote Control  Remote Control |                      |                            |                                |                      |
|   | Input Voltage          | DC 9V-16V   | N/A                  | DC 8V-16V                  | DC 9V-16V                      | N/A                  |
| Iris<br>(Remote Control<br>or Video Auto) | Current Consumption    | Max. 50mA   | N/A                  | Max. 20mA                  | Max. 50mA                      | N/A                  |
|   | Travel Time(End-End)   |   | N/A                  |                            | N/A                            | N/A                  |
|   |                        | N/A   |                      | Approx.>2.0sec.            |                                |                      |
|   | Input Signal           | Video Signal (VS or V)                                      | N/A                  | N/A                        | Video Signal (VS or V)         | N/A                  |
|   | Accuracy               | ±15% at Image Signal  | N/A                  | N/A                        | ±15% at Image Signal           | N/A                  |
|   | Sensitivity Adjustment | 0.5-1.0 Vp-p  | N/A                  | N/A                        | 0.5-1.0 Vp-p                   | N/A                  |
|   | Metering Method        | Average - Peak  | N/A                  | N/A                        | Average - Peak                 | N/A                  |
|   | Response Speed         | Max. 3 sec.   | N/A                  | N/A                        | Max. 3 sec.                    | N/A                  |
| Iris(DC Auto)                             | Drive Coil             | N/A   | 190Ω ±10% (20°C)     |                            |                                | 190Ω ±10% (20°C)     |
|   |                        | N/A   | Close to Open : 4.0V |                            |                                | Close to Open : 4.0V |
|   |                        | N/A   | Open to Close : 0.5V | N/A                        |                                | Open to Close : 0.5V |
|   | Damp Coil              | N/A   | 1150Ω ±10% (20°C)    | N/A                        |                                | 1150Ω ±10% (20°C)    |
|   | Response Speed         | N/A   | Approx. 3 sec.       | N/A                        |                                | Approx. 3 sec.       |
| Zoom                                      | Input Voltage          | DC 8V-16V   |                      |                            |                                |                      |
| (Remote Control)                          | Current Consumption    | Max. 5m   | A (Circuit)          | Max. 80mA (Motor)          |                                |                      |
|   | Operation Speed        | Approx. >3.0vsec. (Entire Range)                            |                      |                            |                                |                      |
| Focus<br>(Remote Control)                 | Input Voltage          | DC 8V-16V   |                      |                            |                                |                      |
|   | Current Consumption    | Max. 5m   |                      | Max. 80mA (Motor)          |                                |                      |
|   | Operation Speed        | Approx. >4.0sec. (Entire Range)                             |                      |                            |                                |                      |
| Auto Focus                                | Focusing Time          | >1.0sec.  |                      | N/A                        |                                |                      |
| Power Supply for Zoom/Focus/              | Input Voltage          | DC 8V-16V   |                      |                            |                                |                      |
| AF/VC/SC                                  | Current Consumption    | Max. 120mA (Stand By) / Max. 300mA (Zoom/Focus/AF On)       |                      |                            |                                |                      |
| Potentiometer for Preset                  |                        | Zoom & Focus (& Iris*)                                      | Zoom & Focus         | Zoom & Fo                  | ocus (& Iris*)                 | Zoom & Focus         |
| Back Focus Adjustment System              |                        | Range : 17.526mm $\pm$ 0.5mm (Option)*                      |                      |                            |                                |                      |
| Optical Axis Adjustment System            |                        | Range : ±0.25mm (Option)*                                   |                      |                            |                                |                      |
| Back Focal Length                         |                        | 11.12mm (in air)  |                      |                            |                                |                      |
| Flange Back Length                        |                        | 17.526mm  |                      |                            |                                |                      |
| Filter Screw Size                         |                        | M62mm P=0.75  |                      |                            |                                |                      |
| Dimension(HxWxD)                          |                        | 78.3 x 84 x 153.7mm   |                      |                            |                                |                      |
| Weight(Approx.)                           |                        | 880g  |                      |                            |                                |                      |